

PRODUCT SPECIFICATIONS

TR2-400

TWO POINT STRAIGHT SIDE TIE ROD



- American brand controls
- Fast acting hydraulic overload system
- High rigidity steel welded frame
- Locked eight point long gibs
- Increased tool life, minimum deflection
- Precision machined components
- Parts and services from BCN Technical Services

TECHNICAL DATA

	MEASUREMENTS
Press Tonnage (US Tons/kN)	450/4000
Tonnage Rating (in./mm)	.28/7
Slide Stroke (in./mm)	11.8/300
Press Speed (spm)	30-50
Stroke Down Adjust Up (in./mm)	31.5/800
Slide Adjustment (in./mm)	11.8/300
Upright Openings F-B (inch/mm)	55/1400
Upright Openings L-R (inch/mm)	126/3200
Slide Area (in./mm)	126x63/ 3200x1600
Bolster Area (in./mm)	126x63/ 3200x1600
Main Motor (HP/KW)	60/45
Overall Dimensions (in./mm)	228x164x252/5800x4200x6400
Total Weight (US Tons /Ton)	112/100

Contact

Bliss Press USA  
1004 East State Street  
Hastings, Michigan 49058 | USA  
P (888) 554-0325  
info@blisspressusa.com  
www.blisspressusa.com