

PRODUCT SPECIFICATIONS

TR2-630

TWO POINT STRAIGHT SIDE TIE ROD



- American brand controls
- Fast acting hydraulic overload system
- High rigidity steel welded frame
- Locked eight point long gibs
- Increased tool life, minimum deflection
- Precision machined components
- Parts and services from BCN Technical Services

TECHNICAL DATA

	MEASUREMENTS
Press Tonnage (US Tons/kN)	693/6300
Tonnage Rating (in./mm)	.40/10
Slide Stroke (in./mm)	13.8/350
Press Speed (spm)	20-40
Stroke Down Adjust Up (in./mm)	39.4/1000
Slide Adjustment (in./mm)	15.7/400
Upright Openings F-B (inch/mm)	63/1600
Upright Openings L-R (inch/mm)	142/3600
Slide Area (in./mm)	142x63/ 3600x1600
Bolster Area (in./mm)	142x63/ 3600x1600
Main Motor (HP/KW)	100/75
Overall Dimensions (in./mm)	315x173x280/8000x4400x7100
Total Weight (US Tons /Ton)	168/150

Contact

Bliss Press USA
1004 East State Street
Hastings, Michigan 49058 | USA
P (888) 554-0325
info@blisspressusa.com
www.blisspressusa.com