

PRODUCT SPECIFICATIONS

TR2-800

TWO POINT STRAIGHT SIDE TIE ROD



- American brand controls
- Fast acting hydraulic overload system
- High rigidity steel welded frame
- Locked eight point long gibs
- Increased tool life, minimum deflection
- Precision machined components
- Parts and services from BCN Technical Services

TECHNICAL DATA

	MEASUREMENTS
Press Tonnage (US Tons/kN)	882/8000
Tonnage Rating (in./mm)	.40/10
Slide Stroke (in./mm)	13.8/350
Press Speed (spm)	20-35
Stroke Down Adjust Up (in./mm)	43.3/1100
Slide Adjustment (in./mm)	15.7/400
Upright Openings F-B (inch/mm)	63/1600
Upright Openings L-R (inch/mm)	157/4000
Slide Area (in./mm)	157.8x71/ 4000x1800
Bolster Area (in./mm)	157.8x71/ 4000x1800
Main Motor (HP/KW)	150/110
Overall Dimensions (in./mm)	343x197x307/8700x5000x7800
Total Weight (US Tons /Ton)	213/190

Contact

Bliss Press USA
1004 East State Street
Hastings, Michigan 49058 | USA
P (888) 554-0325
info@blisspressusa.com
www.blisspressusa.com